

## Technical Data Sheet

Page 1 of 2

<b>Properties:</b>	<p>AKEMI® Thinner/Cleaner P is a product based on low boiling carboxylic acid esters.</p> <p>The product is characterized by the following qualities:</p> <ul style="list-style-type: none"><li>- very high coverage if used as a thinner</li><li>- very high cleaning and degreasing effect</li><li>- very short evaporation time</li><li>- evaporates without residue</li><li>- free of reclaims</li><li>- free of methanol, chlorinated hydrocarbons and paraffinic components</li></ul>
<b>Application Area:</b>	<p>AKEMI® Thinner/Cleaner P is used to dilute AKEMI® Polyester Spray Filler (max. addition 5%). Furthermore, due to its composition the product is best suited to remove fresh sealants, 1-component paints, residues of impregnations as well as grease, oil, wax etc. It can also be used as a degreasing agent for stone surfaces, such as granite, limestone, ceramics etc. which have to be bonded afterwards.</p>
<b>Instructions for Use:</b>	<ol style="list-style-type: none"><li>1. Use as a thinner for AKEMI® Polyester Spray Filler:<ol style="list-style-type: none"><li>a) Add maximum 5% of AKEMI® Thinner/Cleaner P.</li><li>b) Stir the mixture homogenously, then pour into the spray gun and start working.</li></ol></li><li>2. Use as a cleaner:<ol style="list-style-type: none"><li>a) Pour undiluted onto the surface and spread or apply with a cloth, a brush or a suitable pad.</li><li>b) Let the product work for a short period of time and wipe off with a clean and lint-free cloth before the cleaner has evaporated.</li></ol></li></ol>
<b>Special Notes:</b>	<ul style="list-style-type: none"><li>- For professional use only.</li><li>- Use afin® Liquid Glove to protect your hands.</li><li>- Not suitable for plastics and paints which are sensitive to solvents. Test the compatibility on an inconspicuous area before use.</li><li>- Only use on cold surface. Warm surfaces extremely accelerate the evaporation of the solvent and thus reduce the cleaning effect.</li><li>- For proper waste disposal the container must be completely emptied.</li><li>- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.</li></ul>
<b>Technical Data:</b>	<p>Colour: colourless, clear</p> <p>Density: 0.9 g/cm<sup>3</sup></p>
<b>Storage:</b>	<p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 36 months from production.</p>
<b>Health &amp; Safety:</b>	<p>Read Safety Data Sheet before handling or using this product.</p>

TDS 07.22

## Technical Data Sheet

Page 2 of 2

**Important Notice:**

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

---

TDS 07.22